

- ✓ UV Stable
- ✓ Highly Visible
- ✓ Excellent Chemical Resistance
- ✓ Ideal Across Entry Areas

URETHANE FLOOR BUNDING

EASY TO INSTALL, VERSATILE AND DURABLE FLOOR BUNDING

Product	Code	Length	Width	Height
Urethane Floor Bunding Predrilled supplied with 6 screw anchors 8mm x 60mm	CHUFB05	1,000mm	150mm	5mm
Urethane 90° Corner Supplied with 4 screw anchors 8mm x 60mm	CHUFB06	0.2 x 0.2m	150mm	25mm
Sikaflex 11FC Grey 310ml	CHGA1			



APPLICATION EXAMPLES:

- Warehouses
- Liquid storage areas
- Workshops
- Factories
- Filling stations

VERSATILE

Urethane Floor Bunding offers good chemical resistance and is suitable to bund areas containing tanks, drums and equipment. Ideal across doorways and entries. This UV stabilised urethane bunding is flexible yet durable.

WORKPLACE FRIENDLY

The standard yellow colour is highly visible to pedestrians and vehicle traffic alike. Low bund height reduces trip hazards and the profile allows for the comfortable passing of forklifts.

EASE OF INSTALLATION

The lengths and corner pieces are pre-drilled, allowing for easy installation. Minimum tools are required and the urethane bunding can be cut easily. Bunded areas can be quickly configured using the corner pieces.

Before purchasing floor bunding ensure you check ground clearance of forklifts.

For high traffic areas or permanent installations, Spilmax's Aluminium Floor Bunding is recommended.