



ULTRATECH
INTERNATIONAL, INC

Ultra-Spill Pallets

Pull Over Cover Specifications: 13 oz. laminated

Material Description - Base Fabric

Fiber	Polyester
Thickness	.019" (0.48 m/m)
Yarn (Denier)	9/9 (fd/inch)
Fabric Count (threads)	100 yards
Type of Coating	S-PVC

Physical Properties

				Test Method		
		English	Metric	FS-191	ASTM	DIN
Tensile Strength (Strip Method)	Warp	185 lbs/2"	84.1 kg/5cm	FS 5102	ASTM D 5035	DIN 53354
	Fill	167 lbs/2"	75.9 kg/5cm			
Tear Strength (Tongue Method)	Warp	40 lbs	18.2 kg	FS 5134	ASTM D 2261	DIN 53356
	Fill	43 lbs	19.5 kg			
Adhesion Strength		22 lbs/2"		FS 5970	ASTM D 2724	
Temperature Resistance		-22 ~ +160°F	-30 ~ +70°C	--	ASTM D 2136	DIN 53361
Special Features	UV For Exterior Applications, Mildew Resistant. NFPA-701 Fire Rated					

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.