



## SAFETY DATA SHEET

### Section 1 - Chemical Product and Company Information

**Product Name:** Ultra-Repair Putty

**Recommend Use(s):** Ultra-Repair Putty epoxy sticks are used to make emergency patches and repairs of a wide variety of materials.

**Emergency 24-hour Phone (English):** 1-800-424-9300 / 703-527-3887

**Company Information:** UltraTech International, Inc.  
11542 Davis Creek Court  
Jacksonville, Florida 32256 USA

**e-mail:** info@spillcontainment.com  
**Web:** www.spillcontainment.com  
**Telephone:** 800.353.1611 • 904.292.1611 (M-W; 8:00 a.m. - 5:00 p.m. EDT)  
**Fax:** 904.292.1325

### Section 2 - Hazards Identification

**Warning! Irritant:** Product contains chemicals known to cause skin and eye irritation and may cause sensitization by skin contact.

**HS Classification:** Skin corrosion/irritation, Category 2  
Serious eye damage/irritation, Category 2  
Skin sensitisation, Category 1  
Acute aquatic toxicity, Category 3

**Signal Word:** H315 Causes skin irritation  
H319 Causes serious eye irritation  
H317 May cause an allergic skin reaction  
H412 Harmful to aquatic life with long lasting effects

**Precautionary Statements:** P264 Wash hands (skin) thoroughly after handling  
P273 Avoid release to the environment  
P280 Wear protective gloves/protective clothing/eye protection/ face protection  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P303 + P361 IF ON SKIN: Take off contaminated clothing.  
Wash contaminated clothing before reuse.  
P332 + P313 IF SKIN irritation occurs: Get medical advice/attention  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 IF eye irritation persists: Get medical advice/attention  
P501 Dispose of contents and container in accordance with all local, regional, national and international regulations





# SAFETY DATA SHEET

## Section 6 - Accidental Release Measures

**Spill or Leak Procedures:** Wear appropriate personal protective equipment. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place into a designated, labeled waste container. Product should not be released into the environment. Prevent entry into sewers, water courses, basements or confined areas. Dispose of via a licensed waste disposal contractor.

## Section 7 - Handling & Storage

**Handling Precautions:** Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Wear impervious gloves when mixing or handling uncured product. Do not ingest. Avoid contact with eyes, skin and clothing. If sanding cured putty or substrates, wear eye protection and dust mask. For prolonged exposure to sanding dust, wear a half face respirator with dust filters. Wash thoroughly after handling, especially before eating, drinking, smoking and using restroom facilities. Wash contaminated goggles, faceshield and gloves. Professionally launder contaminated clothing before re-use.

**Storage Precautions:** Store in original container protected from direct sunlight in a cool, dry, well ventilated area < 95°F (35°C). Shelf Life: ~2 years (in original tube with cap on)

**General:** The container can be hazardous when empty. Follow label cautions even after the container is empty. Do not re-use empty containers for food, clothing or products for human or animal consumption, or where skin contact can occur.

## Section 8 - Exposure Controls/Personal Protection

**Engineering Controls:** Good general ventilation should be sufficient. Use local exhaust or other engineering controls to keep concentrations below PEL/TLV, or during prolonged sanding operations.

### PERSONAL PROTECTION

**Eyes:** Safety glasses or goggles.

**Respirator:** None required unless sanding or abrading.

**Gloves:** Appropriate impervious gloves. Because a variety of protective gloves exist, consult glove manufacturer to determine the proper type for a specific operation.

**Other:** Ensure that eyewash stations and safety showers are close to the workstation location.

**OSHA HAZARDOUS COMPONENTS (29 CFR 1910.1200):** EXPOSURE LIMITS 8 hrs. TWA (ppm)

Chemical Name	Type	Value
Talc	20 mppcf*	2 mg/m <sup>3</sup> *
Silica, crystalline quartz respirable dust	<u>10 mg/m<sup>3</sup></u> %SiO <sub>2</sub> +2	0.025 mg/m <sup>3</sup>

\*Respirable dust for talc containing no asbestos.



## **SAFETY DATA SHEET**

### **Section 9 - Physical & Chemical Properties**

Appearance:	Putty, gray color after cure.
Odor:	Sulfurous.
Odor Threshold:	Not applicable.
pH:	Not applicable.
Melting Point/Freezing Point:	Not applicable.
Initial Boiling Point and Range:	Decomposition temperature: >302°F (>150°C)
Flash Point:	>200°F (>93°C)
Method:	Setaflash CC.
Evaporation Rate:	Not available.
Flammability Limits:	Not available.
Conditions of Flammability:	Not available.
Explosive Properties:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Relative Density (H <sub>2</sub> O = 1):	1.95
Solubility in Water:	Insoluble in cold and hot water.
Auto-ignition Temperature:	Not available.
Coefficient of Water/Oil Distribution:	Not available.

### **Section 10 - Stability & Reactivity**

General:	This is a stable material.
Conditions of Reactivity:	Under normal conditions of storage and use, hazardous reactions will not occur.
Incompatible Materials and Conditions to Avoid:	Temperatures above 95°F (35°C). Oxidizing agents, acids and bases, amines. For compatibility guide, call 1-800-468-4647.
Hazardous Decomposition:	Nitrogen oxides. Combustion produces oxides of carbon including highly poisonous carbon monoxide. Sulphur oxides.
Hazardous Polymerization:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.



## SAFETY DATA SHEET

### Section 11 - Toxicological Information

ACGIH, A2 - Crystalline silica is a suspected human carcinogen

Target Organs: No specific data

#### POTENCIAL HEALTH EFFECTS:

**Eye Contact:** Causes serious eye irritation. Symptoms may include pain or irritation, watering, redness.

**Ingestion:** Irritating to mouth, throat and stomach.

**Inhalation:** Dusts released from sanding hardened putty may cause irritation to the respiratory tract. Exposure to decomposition products may cause a health hazard. Serous effects may be delayed following exposure.

**Skin Contact:** Causes skin irritation. Symptoms may include irritation, redness.

**LD50:** Not available for mixture.

**LC50:** Not applicable for mixture.

**Carcinogenicity:** Dusts Silica, crystalline quartz:  
IARC: Category 1  
National Toxicology Program: Quartz 14808-60-7  
OSHA: See Section 15  
California Prop 65: Silica, crystalline (non-respirable). Talc, not containing asbestiform fibers.

**Reproduction Toxicity:** Not available.

**Teratogenicity:** Not available.

**Mutagenicity:** Not available.

**Synergistic Products:** Not available.

**Diglycidyl ether of bisphenol A:** Ingestion: The oral LD50 for rats is 11.4 g/kg.  
Skin: Severe irritant, Rabbit: 24 hours 2 Milligrams

**2,4,6-Tri (dimethylaminomethyl) phenol:** Ingestion: The oral LD50 for rats is 1200 mg/kg.  
Skin: The dermal LD50 for rats is 1280 mg/kg.  
Skin: Severe irritant, Rat: 0.25 Milliliters



## **SAFETY DATA SHEET**

### **Section 12 - Ecological Information**

Mobility:	Water contaminating.
Persistence and degradability:	Not inherently biodegradable
Bioaccumulative potential:	Taking into consideration the properties of several components, the product is estimated not to be readily biodegradable according to OECD classification.
Ozone depletion potential:	No ozone depleting chemicals are present or used in manufacture.
Toxicity:	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### **Section 13 - Disposal Considerations**

Waste Disposal Method:	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contactor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
------------------------	---

### **Section 14 - Transport Information**

<b>DOT (Department of Transportation):</b>	
Proper Shipping Name:	Putty, NMFC 150110.
Hazard Class:	Not regulated.
Identification Number:	Not applicable.



## SAFETY DATA SHEET

### Section 15 - Regulatory Information

CERCLA (Comprehensive Environmental Response Compensation and Liability Act): No Reportable Quantity

OSHA Hazard Communication Standard, 29 CFR 1910.1200: Crystalline silica, talc (no asbestos fibers).

SARA Title III (Superfund Amendments and Reauthorization Act):

Crystalline silica non-respirable, Bisphenol-A-epichlorhydrin epoxy resin, 2,4,6-Tri (dimethylaminomethyl) phenol. This product contains zinc compounds which are subject to the reporting requirements of section 313. They constitute approximately 1-5% of the putty.

TSCA (Toxic Substances Control Act): Ingredients of this product are on the Inventory list.

#### STATE REGULATIONS:

Massachusetts: Mineral wool fiber; Soapstone

New Jersey: Soapstone; Silica, quartz; Quartz (SiO<sub>2</sub>); Zinc compounds.

Pennsylvania: Soapstone dust; quartz (SiO<sub>2</sub>); Zinc compounds

### Section 16 - Other Information

#### National Fire Protection Association (NFPA) Hazard Ratings

none → extreme

0 → 4

Health- 2

Flammability- 1

Reactivity- 0

PPE- B

WHMIS Classification: D2B

Reason for Issue: Reviewed, changes to Sections 2, 4, 6, 7 & 16.

Prepared by: Dale Gatehouse, Entreprises Krenda Inc.

Approved by: Mathew Clancy, UltraTech International, Inc.

Previous Date of Issue: 02/24/2015

Revised Date: 02/13/2015

SDS Number: MSD-001

The following is in lieu of all warranties, expressed or implied: All information provided is based on testing and data believed to be accurate.

The information this safety data sheet is believed to be accurate and is the best information available to UltraTech International, Inc. This document is intended only as a guide to the appropriate precautions to handling a chemical by a person trained in chemical handling. UltraTech International makes no warranty of merchantability and any other warranty, express or implied with respect to such information or the product to which it relates, and we assume no liability resulting from the use, misuse or handling of the product to which the safety data sheet relates. Users and handlers of this product should make their own investigations to determine the suitability of the information provided herein for their own purposes.