



**ULTRATECH**  
INTERNATIONAL, INC.

# How To Use The Ultra-Spill Berm Plus Model®

Protective Barrier To Contain, Divert, Or Block Liquids Without Absorbing Them

Follow these easy steps to assure maximum effectiveness:

## I. Deploying the Ultra-Spill Berm Plus®

- a. Use the Ultra-Spill Berm® as desired with the widest base down, making sure no debris interferes with a proper floor seal.
- b. If longer lengths are needed, deploy the additional Ultra-Spill Berm Plus® end-to-end using the built in interlocking connectors, ensuring a proper connection.

## II. Always decontaminate the Ultra-Spill Berm® before reuse or storage.

- a. Wash the Ultra-Spill Berm Plus® using warm water with a non-abrasive detergent or petroleum solvent cleaner.
- b. Dry the Ultra-Spill Berm Plus® before storage.
- c. To repackage the Ultra-Spill Berm Plus® in its response box, start at center, placing the Berm on its side with the widest base facing inward. Allow the Berm to fully relax while repackaging.



## IMPORTANT NOTES

- + Never allow the Ultra-Spill Berm Plus® to touch itself for long periods of time.
- + The Ultra-Spill Berm Plus® will become less flexible if stored in cold temperatures.
- + Due to the nature of softer urethane, the physical properties of these products may change with exposure to certain environmental conditions like temperature, humidity and UV radiation. Please inspect the stored product regularly to ensure it is in a usable state.



These chemicals are compatible for use with the Ultra-Spill Berm Plus®

Acetonitrile	Hydrogen Peroxide (30%)
Aluminum Salts	Jet Fuel (JP-5)
Barium Salts	Kerosene
Benzyl Alcohol	Methanol
Boric Acid	Mineral Oil
Butanol	Naphtha
Calcium Chlorite	Propylene Glycol
Carbon Disulfide	Sodium Hydroxide (50%)
Cupric Chloride	Tetrachloroethylene
Diethylamine	Toluene
Ethyl Acetate	1,1,1-Trichloroethane
Formaldehyde	Trichloroethylene
Gasoline	Triethylamine
Gycol Ether	Turpentine
Hexane	Water

Please visit [www.spillcontainment.com](http://www.spillcontainment.com) for a complete compatibility guide.