

# DRAIN WARDEN

## INSTALLATION INSTRUCTIONS

1. Remove grate and clean drain opening and top lip of the drain. This will ensure a better seal and improve the lifespan of your Drain Warden. Use a grate lifting device if necessary.
2. Rest the grate on its side and tie the Drain Warden onto the underside of the grate. If supplied, tie the absorbent boom onto the grate so it falls in the centre of the basin.
3. Replace the grate back into the drain pit.
4. Trim excess material flush with the grate leaving at least 50mm overhang. If a large gap remains between the grate and the concrete shoulder, fold over the excess geotextile and fold back under to form a filler in the gap.
5. Ensure the grate is correctly replaced and does not create a trip hazard.



## MAINTENANCE

1. Inspect the Drain Warden after every event that results in stormwater discharge from the site.
2. During inspection, remove any solids that have been captured by the Drain Warden.
3. The absorbent boom should be replaced on a frequent basis (3-6 months) to ensure efficient absorption.

## DISPOSAL INSTRUCTIONS

1. The absorbent boom should be drained prior to disposal.
2. The Drain Warden can typically be disposed of via general waste; although subject to local government requirements.

### Disclaimer

The Manufacturer and its distributors are not liable for any product failures relating to installation, deliberate misuse of the product, or damage caused by vehicle usage or accidents. It is the owner's responsibility to ensure that all site engineering and safety standards are met during handling and installation, and where necessary, appropriate consultants are engaged to provide the necessary technical advice and to ensure that the substrate is structurally suitable for a secure and sealed bund.



Spill Containment  
on Land



Spill Containment  
on Water



Liquid Containment



Stormwater  
Protection



Silt & Sediment  
Control



Bags & Covers



Water Diversion



Spill Control