



## Flexible Floor Bunding


Spill Containment on Land

### 150mmH High Profile Flexible Floor Bunding

A containment-first bund wall for dedicated spill zones where volume and boundary control matter most. Heavy duty 900 gsm hi vis PVC with chemical resistance, plus UV resistance and a 5-year warranty for outdoor

Product Code	Description	Length	Width	Height
CHFFB41	Flexible Floor Bunding	2m	205mm	150mm
CHFFB42	Flexible Floor Bunding 90° Corner Join	300mm	205mm	150mm
CHFFB38	Installation Kit 2mL	Aluminium Flat Bar, Nylon Anchor and Sealant		

Specifications	
Material Type	Heavy Duty Hi-Vis PVC
Material Weight	900 gsm
Chemical Resistant	Yes
UV Resistant	Yes, 5 Year Warranty



#### Best Fit For

- Hazardous liquids storage zones where escaping liquid must be prevented
- Plant rooms, generator rooms, battery storage, or banded storage where traffic can be rerouted
- Outdoor containment lines where UV resistance matters

#### Not Suitable For

- Across doorways or frequent access points
- Any drive over requirement
- Sites needing permanent fixed bunding to replace civil works



**DISCLAIMER:** Chatoyer is not responsible for any product malfunctions, damage, or performance issues resulting from misuse, unauthorised modifications, improper installation, external environmental factors, or failure to follow recommended usage guidelines. This includes, but is not limited to, damage caused by accidents, natural disasters, power surges, or use with incompatible accessories. All warranties and support services apply only to products used in accordance with the manufacturer's instructions and within the intended operating conditions.



# CHATOYER

WWW.CHATOYER.COM.AU | 1300 880 623

NSW 351 Wentworth Avenue, Pendle Hill, NSW 2145 QLD 2/27 Service St Maroochydore QLD 4558

VERSION 280126