




Flexible Floor Bunding

Spill Containment on Land

75mmH Medium Profile Flexible Floor Bunding

Build small banded zones that can still be crossed at low speed by forklifts without load disruption, using the triangular profile that compresses under vehicle weight and returns to shape.

Product Code	Description	Length	Width	Height
CHFFB03	Flexible Floor Bunding	5m	205mm	75mm
CHFFB01	Flexible Floor Bunding	10m	205mm	75mm
CHFFB02	Flexible Floor Bunding	30m	205mm	75mm
CHFFB29	90° Corner Join	300mm	205mm	75mm
CHFFB36	Installation Kit 5mL	Screws, Aluminium Flat Bar and Sealant		
CHFFB37	Installation Kit 10mL			
CHFFB08	Installation Kit 90° Corner Join	Screws		



Specifications	
Material Type	Heavy Duty Hi-Vis PVC
Material Weight	900 gsm
Chemical Resistant	Yes

Best Fit For

- Low speed forklift crossings into banded work bays and maintenance zones
- Transfer or decanting points where you want more containment height without blocking access
- Warehouse operational areas where a visible boundary helps keep spills in zone

Not Suitable For

- High speed travel lanes or continuous traffic cycles
- Heavily loaded equipment with limited ground clearance
- Sites needing rigid bund walls or permanent civil works

DISCLAIMER: Chatoyer is not responsible for any product malfunctions, damage, or performance issues resulting from misuse, unauthorised modifications, improper installation, external environmental factors, or failure to follow recommended usage guidelines. This includes, but is not limited to, damage caused by accidents, natural disasters, power surges, or use with incompatible accessories. All warranties and support services apply only to products used in accordance with the manufacturer's instructions and within the intended operating conditions.



CHATOYER

WWW.CHATOYER.COM.AU | 1300 880 623

NSW 351 Wentworth Avenue, Pendle Hill, NSW 2145 QLD 2/27 Service St Maroochydore QLD 4558

VERSION 280126