



Aluminium Floor Bunding

Spill Containment on Land

SOLID, ROBUST, AND EASY TO INSTALL FLOOR BUNDING

Aluminium Floor Bunding is fire-resistant, non-sparking, and compliant with AS 1940-2004 for flammable liquid containment. Made from marine grade 5 aluminium, it handles 10 tonnes per axle. The 33mm low profile with traction grooves ensures smooth vehicle access. Supplied in 1200mm lengths with installation kit. Optional hi-vis powder-coating boosts visibility; rubber seals enhance sealing on uneven surfaces. Durable, cost-effective, and long-lasting.

| Product Code | Description | Length | Width | Height |
|--------------|--|---|-------|--------|
| CHAFB01 | Aluminium Floor Bunding (1.2mL x 184mmW x 30mmH) predrilled with 4 Screw Anchors | 1.2m | 185mm | 30mm |
| CHAFB04 | Yellow Powder Coat | (minimum 15 pieces) | | |
| CHAFB03 | Charge for 1 x Straight or 45 Mitre Cut | Outside of these angles, additional charges will apply. | | |
| CHGA01 | SikaFlex 11FC Grey 310ml | | | |



Optional Hivis Powder Coated option shown above

| Specifications | |
|-----------------------|--|
| Material Type | Marine Grade 5 extruded aluminium |
| Material Weight | 7 kg |
| Standard Length | 1200mm |
| Load Capacity | 10 tonnes per axle |
| Fire Resistant | Yes |
| Vehicle Compatibility | Suitable for Class 2 RAV B-Doubles, container forklifts, and other heavy vehicles. |

APPLICATION

- Industrial areas with heavy duty machinery
- High frequency traffic areas
- Class 3 Flammable Liquid Storage Areas
- Warehouses, doorways and access points
- Wash bays

DISCLAIMER: Chatoyer is not responsible for any product malfunctions, damage, or performance issues resulting from misuse, unauthorised modifications, improper installation, external environmental factors, or failure to follow recommended usage guidelines. This includes, but is not limited to, damage caused by accidents, natural disasters, power surges, or use with incompatible accessories. All warranties and support services apply only to products used in accordance with the manufacturer's instructions and within the intended operating conditions.



CHATOYER

WWW.CHATOYER.COM.AU | 1300 880 623

NSW 351 Wentworth Avenue, Pendle Hill, NSW 2145 QLD 2/27 Service St Maroochydore QLD 4558

VERSION 170725