



Chatoyer Dewatering Bag

Silt and Sediment Control

EFFICIENT SEDIMENT CONTROL DURING DEWATERING OPERATIONS

The Geobag dewatering and sediment filter bags are perfect for pumping and filtering sediment laden water. Our standard range of dewatering bags provide a simple yet effective method of removing heavy particles (>180 microns) and absorbing hydrocarbons from excavation water allowing silt and hydrocarbon free water to be released from the bag.

Product Code	Description	Length	Width	Neck
CHDWB02	Dewatering Bag	1.2m	1.2m	100mm
CHDWB03	Dewatering Bag	2.5m	1.5m	200mm

Specifications	
Material	270gsm, Non-woven geotextile
Pore Size	180 microns
UV Resistance	70% strength retained after 500 hours
Flow Rate	60L/m ² /s
Filter Efficiency	99%



APPLICATION

- Small to medium excavation sites
- Pump outs of standing water
- Aggregate wash downworks

DISCLAIMER: Chatoyer is not responsible for any product malfunctions, damage, or performance issues resulting from misuse, unauthorised modifications, improper installation, external environmental factors, or failure to follow recommended usage guidelines. This includes, but is not limited to, damage caused by accidents, natural disasters, power surges, or use with incompatible accessories. All warranties and support services apply only to products used in accordance with the manufacturer's instructions and within the intended operating conditions.



CHATOYER

WWW.CHATOYER.COM.AU | 1300 880 623

NSW 351 Wentworth Avenue, Pendle Hill, NSW 2145 QLD 2/27 Service St Maroochydore QLD 4558