



Silt Curtain

Silt and Sediment Control

Stay Compliant with Our Silt and Sediment Control Products

Reliable performance is essential when environmental protection is required. These silt curtains have proven their quality since 2009. Standard curtain length is 20m, with custom lengths and depths available. Designs can be tailored to suit water conditions, handling needs, deployment duration, visibility, and regulatory requirements.

Product Code	Description	Length	Draft	Freeboard
CHSC111	Class 1 Connected	20m	1m	100mm x 50mm
CHSC112	Class 1 Connected	20m	2m	100mm x 50mm
CHSC113	Class 2 Connected	20m	1m	100mm x 100mm
CHSC114	Class 2 Connected	20m	2m	100mm x 100mm
CHCONN02	Silt Curtain Class 2 Connector			
CHCHAN29	Silt Curtain Rigging Set 15mL 8mm Silver Rope			
AMCTOW02	Tow Bridle (900mmL x 310mmH) Marine SS316 Wire Rope 6mm			



Specification	Value
Fabric	400gsm Hi-Vis Yellow PVC 260gsm Nonwoven Geotextile with High Filtration Capacity
Flotation Chambers	Closed Cell Crumble Free Foam Flotation
Connector	Standard Universal ASTM F962 Z-Connectors
Locking Mechanism	Toggle Pin
Ballast Chain	6mm Galvanised Chain Ballast Enclosed in PVC Pocket
UV Resistant	Yes up to 5 years



APPLICATION

- Marine and Coastal Projects
- Inland Waterways
- Infrastructure and Civil Works
- Environmental Protection Zones

DISCLAIMER: Chatoyer is not responsible for any product malfunctions, damage, or performance issues resulting from misuse, unauthorised modifications, improper installation, external environmental factors, or failure to follow recommended usage guidelines. This includes, but is not limited to, damage caused by accidents, natural disasters, power surges, or use with incompatible accessories. All warranties and support services apply only to products used in accordance with the manufacturer's instructions and within the intended operating conditions.



CHATOYER

WWW.CHATOYER.COM.AU | 1300 880 623

NSW 351 Wentworth Avenue, Pendle Hill, NSW 2145 QLD 2/27 Service St Maroochydore QLD 4558