



Ultra-Drain Guard Adjustable Frame

Stormwater Protection

SECURE CATCH BASIN INSERT THAT STAYS IN PLACE

Ultra-Drain Guard Adjustable Frame provides reliable sediment and debris capture in stormwater drains. Its adjustable steel frame resizes to suit most drain openings and prevents the filter from falling into the basin, even when the grate is removed. With no excess fabric to trim, it delivers a clean, professional installation and quick, hassle-free maintenance.

Product Code	Description	Length	Width	Height
CHU8930	Drain Guard Adjustable Frame	0.5m	0.4m	450mm
CHU8932	Drain Guard Adjustable Frame Replacement Filter 10 pack			

Specifications	
Oil Absorption Capacity	2L
Sediment Load Capacity	18kg
Material	270gsm, Non-woven, Polypropylene Geotextile
Filter Upgrade	Ultra-Filter-Tex
UV Resistance	70% strength retained after 500 hours
Pore Size	177 microns
Flow Rate	60L/m ² /sec



APPLICATION

- Construction and civil works sites
- Stormwater drains and catch basins
- Roadworks and infrastructure projects
- Sediment and erosion control zones
- Temporary environmental compliance areas

DISCLAIMER: Chatoyer is not responsible for any product malfunctions, damage, or performance issues resulting from misuse, unauthorised modifications, improper installation, external environmental factors, or failure to follow recommended usage guidelines. This includes, but is not limited to, damage caused by accidents, natural disasters, power surges, or use with incompatible accessories. All warranties and support services apply only to products used in accordance with the manufacturer's instructions and within the intended operating conditions.



CHATOYER

WWW.CHATOYER.COM.AU | 1300 880 623

NSW 351 Wentworth Avenue, Pendle Hill, NSW 2145 QLD 2/27 Service St Maroochydore QLD 4558

VERSION 150126