



Ultra-Drain Guard Oil & Sediment

Stormwater Protection

STORMWATER FILTRATION FOR OIL AND SEDIMENT CONTROL

The Ultra-Drain Guard Oil & Sediment is a catch basin insert designed to capture hydrocarbons, sediment and litter from stormwater runoff. Ideal for industrial, construction and car park environments, it helps protect drainage systems and waterways by filtering oil, fuel, sand and debris before they enter the stormwater network.

Product Code	Description	Length	Width	Height	Oil Absorption Capacity
CHU7140	Drain Guard - Oil and Sediment	1.2m	1.2m	450mm	4L
CHU7141	Drain Guard - Oil and Sediment, Plus	1.2m	1.2m	450mm	6L

Specifications	
Sediment Load Capacity	18kg
Product Material Weight	270gsm
Pore Size	180 microns
UV Resistance	70% strength retained after 500 hours
Flow Rate	60L/m ² /s
Permittivity	1.50 sec ⁻¹
Puncture Resistance	238kg



APPLICATION

- Industrial facilities
- Construction sites
- Car parks and service areas

DISCLAIMER: Chatoyer is not responsible for any product malfunctions, damage, or performance issues resulting from misuse, unauthorised modifications, improper installation, external environmental factors, or failure to follow recommended usage guidelines. This includes, but is not limited to, damage caused by accidents, natural disasters, power surges, or use with incompatible accessories. All warranties and support services apply only to products used in accordance with the manufacturer's instructions and within the intended operating conditions.



CHATOYER

WWW.CHATOYER.COM.AU | 1300 880 623

AUSTRALIAN MASTER DISTRIBUTOR OF ULTRATECH INTERNATIONAL, INC.