



Ultra-Repair Putty

Spill Control

FAST, DURABLE, ALL-PURPOSE REPAIRS

Ultra-Repair Putty provides rapid, high-strength repairs on steel, glass, masonry and most plastics. It kneads easily and cures to a steel-hard finish within one hour, making it ideal for sealing leaks, filling cracks and rebuilding damaged surfaces. Designed for reliability in demanding environments, it is an essential addition to spill response and maintenance kits.

Product Code	Description	Length	Width	Height	Weight
CHU2120	Repair Putty, 12 Sticks Per Box	177mm	22mm	22mm	2kg

Specifications	
Density	1.8 kg/L
Hardness (Shore D)	85
Temperature	Intermittent: 149°C; Continuous: 121°C
Storage	Exothermic reaction at 51° C. Unaffected by cold. Best used when warm.
Shelf Life	Several years if stored in original tube with cap on.



APPLICATION

- Sealing leaks in drums, tanks and containers
- Rebuilding worn or cracked equipment surfaces
- Emergency pipe and joint repairs
- Bonding metal, plastic or masonry components

DISCLAIMER: Chatoyer is not responsible for any product malfunctions, damage, or performance issues resulting from misuse, unauthorised modifications, improper installation, external environmental factors, or failure to follow recommended usage guidelines. This includes, but is not limited to, damage caused by accidents, natural disasters, power surges, or use with incompatible accessories. All warranties and support services apply only to products used in accordance with the manufacturer's instructions and within the intended operating conditions.



CHATOYER

WWW.CHATOYER.COM.AU | 1300 880 623

NSW 351 Wentworth Avenue, Pendle Hill, NSW 2145 QLD 2/27 Service St Maroochydore QLD 4558